

Application No. 10/693,569  
Amendment dated 06/11/2007 responding to Office Action dated 02/09/2007

RECEIVED  
CENTRAL FAX CENTER  
JUN 11 2007

**AMENDMENTS**

**In the Claims**

Please amend claims 1, 3, 4, and 15 and cancel claim 20 as follows. The following listing of claims will replace all prior versions and listings of claims in the application.

Application No. 10/693,569

Amendment dated 06/11/2007 responding to Office Action dated 02/09/2007

RECEIVED  
CENTRAL FAX CENTER

JUN 11 2007

LISTING OF THE CLAIMS

1 **1.** (Presently Amended) A car audio amplifier system for use with a head unit of an  
2 automobile, the amplifier system comprising:

3 (A) a control unit couplable to the head unit and including,

4 (1) at least one input connector for receiving at least one respective channel of  
5 audio signal from the head unit ~~a source~~,

6 (2) circuitry, coupled to receive the audio signal from the input connector, for  
7 modifying the received audio signal;

8 (3) at least one control for determining a characteristic of the modifying; and

9 (4) at least one output connector for outputting the modified audio signal; and

10 (B) an amplifier unit physically separate from, and coupled ~~couplable~~ to, the control unit  
11 and including,

12 (1) an input connector for receiving the modified audio signal output from the  
13 control unit,

14 (2) amplification circuitry coupled to the input connector for amplifying the  
15 modified audio signal, and

16 (3) an output connector for outputting the amplified modified audio signal to a  
17 loudspeaker.

1 **2.** (Original) The car audio amplifier system of claim 1 wherein:  
2 the circuitry of the control unit includes a pre-amplifier.

1 **3.** (Presently Amended) The car audio amplifier system of claim 1 wherein:  
2 the input connector of the control unit is further for receiving at least two channels of  
3 audio signal from the head unit ~~source~~;  
4 the output connector of the control unit is further for outputting at least two channels of  
5 modified audio signal; and

Application No. 10/693,569

Amendment dated 06/11/2007 responding to Office Action dated 02/09/2007

6 the circuitry of the control unit includes means for combining two channels of audio  
7 signal from the head unit source and providing the combined signal to one channel at the output  
8 connector of the control unit.

1 4. (Presently Amended) The car audio amplifier system of claim 3 wherein:

2 the two channels of audio signal from the head unit source include a Left channel and a  
3 Right channel; and

4 the circuitry of the control unit provides a modified Left channel signal to a Front Left  
5 channel and a Rear Left channel at the control unit's output connector, a modified Right channel  
6 signal to a Front Right channel and a Rear Right channel at the control unit's output connector,  
7 and a combination of the modified Left channel signal and the modified Right channel signal to  
8 one of a Center channel and a Subwoofer channel at the control unit's output connector.

1 5. (Original) The car audio amplifier system of claim 1 wherein:

2 the amplifier unit includes a plurality of input connectors; and

3 the amplifier circuitry amplifies audio signals provided at a selected one of the plurality  
4 of input connectors.

1 6. (Original) The car audio amplifier system of claim 5 wherein:

2 the amplifier unit includes a first input connector comprising a set of RCA jacks, and a  
3 second input connector comprising a DIN connector.

1 7. (Original) The car audio amplifier system of claim 1 wherein:

2 all of the controls of the audio amplifier system are located on the control unit.

1 8. (Original) The car audio amplifier system of claim 1 wherein the characteristic comprises  
2 gain.

1 9. (Original) The car audio amplifier system of claim 1 wherein:

2 the control unit comprises a plurality of controls each for determining a respective one of  
3 a plurality of characteristics; and

4 the plurality of characteristics comprises gain and at least one of high pass filter, low pass  
5 filter, delay, phase, subsonic filter, subwoofer parametric frequency, and bass boost.

Application No. 10/693,569

Amendment dated 06/11/2007 responding to Office Action dated 02/09/2007

1 10. (Original) The car audio amplifier system of claim 1 wherein:

2 the amplifier unit comprises a docking bay adapted for docking the control unit.

1 11. (Original) The car audio amplifier system of claim 10 wherein:

2 the docking bay comprises an input connector adapted to mate with the output connector  
3 of the control unit when the control unit is docked.

1 **12.** (Original) An amplifier system for use in a vehicle which includes a passenger

2 compartment having a head unit providing a plurality of audio channel signals, the amplifier  
3 system comprising:

4 (A) a control unit adapted to mount in the passenger compartment, and comprising,  
5 a control unit input connector for receiving the plurality of audio channel signals  
6 from the head unit,

7 a plurality of controls including at least a gain control,  
8 circuitry, coupled to the control unit input connector, for modifying the plurality  
9 of audio signals in response to settings of the controls, and

10 a control unit output connector for outputting the plurality of modified audio  
11 signals; and

12 (B) an amplifier unit comprising,

13 an amplifier input connector coupled to the control unit output connector to  
14 receive the modified audio signals,

15 amplifier circuitry coupled to the amplifier input connector for amplifying the  
16 modified audio signals; and

17 speaker terminals coupled to the amplifier circuitry for outputting the amplified  
18 modified audio signals.

1 13. (Original) The amplifier system of claim 12 further comprising:

2 a cable coupling the amplifier input connector to the control unit output connector.

Application No. 10/693,569

Amendment dated 06/11/2007 responding to Office Action dated 02/09/2007

1 14. (Original) The amplifier system of claim 13 wherein:

2 the control unit output connector comprises a DIN connector, the amplifier input  
3 connector comprises a DIN connector, and the cable comprises a DIN umbilical cable.

1 15. (Presently Amended) The amplifier system of claim 12 wherein the plurality of controls  
2 comprises all of ~~off~~ the amplifier system's gain controls.

1 16. (Original) The amplifier system of claim 12 wherein the plurality of controls further includes  
2 a filter control.

1 17. (Original) The amplifier system of claim 16 wherein the plurality of controls further includes  
2 a delay control.

1 18. (Original) The amplifier system of claim 17 wherein the plurality of controls further includes  
2 a phase control.

1 19. (Original) The amplifier system of claim 18 wherein the plurality of controls further includes  
2 a bass boost control.

1 20. (Cancelled)

1 21. (Original) The amplifier system of claim 12 wherein the plurality of controls further includes  
2 a multi-channel equalizer.

1 22. (Original) The amplifier system of claim 12 wherein the control unit further includes:  
2 an auxiliary input connector for receiving audio channel signals from an auxiliary unit;  
3 and  
4 an input selector control for selecting whether the circuitry modifies the audio channel  
5 signals from the input connector or the audio channel signals from the auxiliary input connector.

1 23. (Original) The amplifier system of claim 22 wherein the control unit further includes:  
2 input volume means for compensating for signal level difference between audio channel  
3 signals from the input connector and audio channel signals from the auxiliary input connector,

Application No. 10/693,569

Amendment dated 06/11/2007 responding to Office Action dated 02/09/2007

4 whereby when a user switches between the head unit and the auxiliary unit by operating the input  
5 selector control, a difference in audio volume from the loudspeakers is controlled.

1 24. (Original) The amplifier system of claim 12 wherein:

2 the amplifier unit includes a docking bay into which the control unit can be docked; and

3 means for connecting the control unit output connector to the amplifier input connector.

1 25. (Original) The amplifier system of claim 12 wherein the plurality of audio channel signals  
2 provided by the head unit includes Front Left, Front Right, Center, Rear Left, Rear Right, and  
3 Subwoofer audio channel signals, and wherein the plurality of controls comprises:

4 Front gain,

5 Front high pass filter,

6 Center gain,

7 Center high pass filter,

8 Center delay,

9 Rear gain,

10 Rear high pass filter,

11 Rear delay,

12 Subwoofer gain,

13 Subwoofer low pass filter,

14 Subwoofer phase,

15 Subwoofer subsonic filter,

16 Subwoofer parametric frequency, and

17 Subwoofer bass boost.

Application No. 10/693,569

Amendment dated 06/11/2007 responding to Office Action dated 02/09/2007

1       **26.** (Original)       A method whereby a person adjusts audio characteristics of an audio  
2       system, the audio system having a head unit, a control unit coupled to the head unit, an external  
3       amplifier coupled to the control unit, and loudspeakers coupled to the external amplifier, all  
4       channel gain controls for the amplifier being located on the control unit, wherein the head unit,  
5       the control unit, and the loudspeakers are located within a passenger compartment of a vehicle,  
6       the method comprising:  
7               being positioned within the passenger compartment;  
8               operating the head unit to provide a plurality of audio channel signals to the control unit;  
9               while listening to sound produced by the loudspeakers which are driven by the external  
10       amplifier according to modified audio channel signals from the control unit,  
11               adjusting a control on the control unit, to control a modification by the control  
12       unit of one of the audio channel signals provided by the head unit, until a desired acoustic  
13       result is obtained by such adjusting.

1       27. (Original) The method of claim 26 wherein:  
2               adjusting the control comprises adjusting a channel gain control.

1       28. (Original) The method of claim 27 wherein:  
2               adjusting the control further comprises adjusting a channel filter control.

1       29. (Original) The method of claim 28 further comprising:  
2               selecting back and forth between audio signals provided by the head unit and audio  
3       signals provided by an auxiliary unit; and  
4               adjusting an input level adjustment control on the control unit, to substantially equalize  
5       an audio volume produced in response to the audio signals provided by the head unit and an  
6       audio volume produced in response to the audio signals provided by the auxiliary unit.

1       30. (Original) The method of claim 26 further comprising:  
2               removing the control unit from the passenger compartment; and  
3               docking the control unit into a docking bay on the external amplifier.